



product
information

6SLA-200
FLOW & ANTI-CRATER ADDITIVE

Cardinal's **6SLA-200** is a Flow and Anti-Crater additive designed for use in our 6S00, 6100, 6200, 6300, 6400 and 6700 series two component Polyurethanes. 6SLA-200 lowers surface tension which improves the surface properties at the substrate-coating interface.

TYPICAL USES:

- Anti-Crater additive
- Flow additive

BENEFITS:

- Easy incorporation

Safety:

Contains organic solvents. Use with adequate ventilation - do not breath vapors or spray mists. If component TLVs are exceeded, a NIOSH approved air supplied respirator is advised. See MSDS for TLV information. Allergic reactions are possible. Avoid use by persons with respiratory problems. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

FIRST AID:

Eye contact, flush immediately with plenty of water for at least 15 min. and get medical attention.
Skin contact.: wash thoroughly with soap and water for 5 minutes.
If swallowed, do not induce vomiting and get medical attention immediately.
Inhalation, remove to fresh air.

TYPE: Anti-Crater Additive

COMPONENTS: One

MINIMUM ORDER: 1 quart

VOC CONTENT: (AS SUPPLIED)

507 GRAMS/LITER (4.22 LBS/GAL)
101 GRAMS/LITER (0.81 LBS/GAL)

VOLUME SOLIDS: 13 %

FLASH POINT: -4°F TCC

SHELF LIFE: 6 months from date of manufacture on the container.

MIXING RATIO: Add one (1) to two (2) ounces of 6SLA-200 of catalyzed High Solids Polyurethane coating. Add 6SLA-200 with agitation to reduce the possibilities of cratering.

APPLICATION:

6SLA-200 will not affect the application properties of the coating.

CLEAN-UP: Clean up should be done as soon as possible. Air quality regulations may limit allowable emissions from cleaning operations.

PRODUCT LIMITATIONS:

- For industrial use only.

FOR INDUSTRIAL USE ONLY
NOT FOR RESIDENTIAL USE

J15TL

So. El Monte, CA 1329 Potrero Ave. 91733 (323) 283-9335 (626) 444-9274 Fax (626) 444-0382

www.cardinalpaint.com

IMPORTANT: Warranty and Disclaimer— The performance characteristics of these products vary according to product application, operating conditions, materials applied to or with and use. Since these factors can affect results, we strongly recommend that you make your own test to determine to your satisfaction whether the product is of acceptable quality, has not been affected by storage or transport and is suitable for your particular purpose under your own operation conditions prior to using any product in full scale production. Seller warrants the products to be free from defects in materials and workmanship. SUCH WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE. No representative of ours has authority to waive or change this provision, which applies to all sales of these products.