

SAFETY DATA SHEET



DATE ISSUED :	6/29/2015
SDS REF. No :	EL-005

EL-005 POLYURETHANE ACCELATOR

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: EL-005 POLYURETHANE ACCELATOR

PRODUCT CODE: EL-005

PRODUCT USE: Polyurethane Accelerator

MANUFACTURER

Cardinal Industrial Finishes
1329 Potrero Ave

S. El Monte, CA,
626 444-9274

24 HR. EMERGENCY TELEPHONE NUMBER

CHEMTREC (US Transportation): (800)424-9300

CHEMTREC (International : 1(202)483-7616

Transportation)

WEB: WWW.CARDINALPAINT.COM

2. HAZARDS IDENTIFICATION

PICTOGRAMS



SIGNAL WORD : DANGER

HAZARD STATEMENTS : H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H311 Toxic in contact with skin or if inhaled.

H317 May cause an allergic skin reaction.

H314 Causes severe skin burns eye damage.

H341 Suspected of causing genetic defects.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS : P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P363 Wash contaminated clothing before reuse.

Collect spillage.

P405 Store locked up.

P501 Dispose of in accordance with Local, Regional, State, Federal, and International Regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number	
Acetylacetone	95% - 100%	123-54-6	
Dibutyltin Dilaurate	1% - 5%	77-58-7	

4. FIRST AID MEASURES

Description of first and measures.

EYES CONTACT : Flush with large quantities of water for 15 to 30 minutes. Remove contact lenses. Keep eyes wide open while rising. If eye irritation persists: Get medical attention.

SKIN CONTACT : Wash exposed area with mild soap and water for 15 to 30 minutes. Remove contaminated clothing. Repeated exposure may cause dryness or cracking.

INGESTION : Rinse mouth. Do NOT induce vomiting. Keep victim warm and seek immediate attention.

INHALATION : Remove to fresh air and keep in a position comfortable to breath. Call a doctor/physician if you feel unwell. Get medical attention.

Most important symptoms and effects, both acute and delayed. Symptoms/injuries: Eye irritation

Symptoms/injuries after inhalation: May cause drowsiness or dizziness.

Symptoms/injuries after eye contact: Cause serious eye irritation.

Symptoms/injuries after ingestion: Ingestion may cause nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed.

If medical advise is needed, have product container or label on hand.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : In the event of a fire, use specifically suitable extinguishing agents. Suitable extinguishing media: Foam, alcohol resistant foam, CO2, water fog. Unsuitable extinguishing media: Do not use heavy water stream. A heavy water stream may spread burning liquid.

FIRE FIGHTING PROCEDURE : Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering the environment.

Protection during firefighting: Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure modes.

UNUSUAL FIRE AND EXPLOSION HAZARD : Fire hazard: Highly flammable/liquid or vapor.

Explosive hazard: May form flammable/explosive vapor-air mixture.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES :

General measures: Remove ignition sources. Use special care to avoid static electric charges. No smoking.

FOR NON-EMERGENCY PERSONNEL :

For non-Emergency procedures: Evacuate unnecessary personnel.

FOR EMERGENCY RESPONDERS :

Equip cleanup crew with proper protection. Avoid breathing fume, vapors.

ENVIRONMENTAL PRECAUTIONS :

Prevent entry to sewers and public waters.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEAN UP :

Collect damaged aerosols and use absorbent and/or inert material, then place in suitable container.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING : Additional hazards when processed: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when you are leaving work. Provide good ventilation in process area to prevent formation of vapor. No smoking. Use only non-sparking tools. Use outdoors or in a well ventilated area. Avoid breathing fume, vapors.

Hygiene measures: Wash Skin thoroughly after handling.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES : Storage conditions: Store in a dry, cool and well-ventilated place away from: Heat sources. Direct sunlight.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Source of ignition. Direct sunlight. Heat Sources.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Dibutyltin Dilaurate(77-58-7)		
USA ACGIH	ACGIH STEL	0.2 mg/m3
USA ACGIH	ACGIH TWA	0.1 mg/m3
USA NIOSH	NIOSH REL	0.1 mg/m3
USA OSHA	OSHA PEL (Table Z-1)	0.1 mg/m3
USA OSHA	OSHA TWA (Table Z-1A)	0.1 mg/m3

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION : If TLV of the product or any component is exceeded, a NIOSH approved dust respirator is advised in absence of environmental control. OSHA Regulations also permit other NIOSH dust respirators under specified conditions. (See your Safety Equipment Supplier) Engineering or administrative controls should be implemented to reduce exposure.

HAND PROTECTION REMARKS : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

EYES PROTECTION : Eye wash bottle with pure water.

Tightly fitting safety goggles.

Where face-shield and protective suit for abnormal processing problems.

SKIN AND BODY PROTECTION : Wear impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

WORK HYGIENIC PRACTICES: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Liquid
Color	:	Various colors depending on the pigmentation.
Odor	:	Chartistic. Sweet. Mint like.
Odor threshold	:	No data available.
Ph	:	N/A - See Technical Data Sheet
Evaporation rate	:	Slower Than Ether
Melting point	:	-94.7 C (-138.46 F)
Freezing point	:	No data available.
Boiling point	:	285.0 deg F TO 285.0 deg F
Flash point	:	96.00 deg F deg F
Lower explosion limit	:	2.4
Upper explosion limit	:	11.4
Vapour pressure	:	185 mm Hg
Vapour density	:	Heavier than air
Relative density	:	No data available.
Density	:	8.5719
Solubility	:	No data available.
Partion coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available.
Decomposition temperature	:	No data available.

10. STABILITY AND REACTIVITY

REACTIVITY : No dangerous reaction known under conditions of normal use.

CHEMICAL STABILITY : Stable under normal conditions.

CONDITIONS TO AVOID : Extremely high temperatures, poor ventilation and excessive aging.

INCOMPATIBLE MATERIALS : Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

11. TOXICOLOGICAL INFORMATION

Dibutyltin Dilaurate(77-58-7)	
Chronic Health Hazard	Dibutyltin compounds have shown reproductive and immunotoxic effects in laboratory animals. Abnormalities noted at necropsy of animals treated with 2000 mg/kg of dibutyltin dilaurate were hemorrhagic lungs, dark liver, dark kidneys, haemorrhage of gastric mucosa, haemorrhage of the large and small intestines, enlarged bile duct and behavioral and central nervous system effects. Decreased fertility was seen in hens following dietary administration equal to 78 mg/kg.
Eye irritation/corrosion	Severe eye irritation.
Inhalation	No data is available on the product itself.
LD50 - Rabbit (Dermal)	> 2,000 mg/kg, Method : Estimated.
LD50 - Rat (Ingestion)	> 2,000 mg/kg
Skin irritation/corrosion	Severe skin irritation. Corrosive to the skin of a rabbit.

12. ECOLOGICAL INFORMATION

Dibutyltin Dilaurate(77-58-7)	
Aquatic toxicity	No data is available on the product itself.
Bioaccumulation	No data is available on the product itself.
EC50 - Daphnia	2.28 mg/l, Species : Daphnia magna.
LC50 - Fish	2 mg/l, Species : Fish.
Mobility	No data available.
Persistence and degradability	Biodegradability : No data is available on the product itself.
Toxicity to other organisms	No data available.

13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

GENERAL INFORMATION : No data available.

DISPOSAL METHOD: Dispose of waste and residues in accordance with Local, State, and Federal Regulations. Mix with compatible chemical which is less flammable and incenerate. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind or weld or near this container.

14. TRANSPORT INFORMATION

***CHECK WITH YOUR CARRIER FOR ADDITIONAL RESTRCITIONS THAT MAY APPLY.**

USDOT GROUND

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME (DOT) : Paint Related Material

HAZARDS CLASS : 3

UN/NA NUMBER : UN1263

PACKING GROUP : PG II

EMERGENCY RESPONSE GUIDE (ERG) : 127

IATA (AIR)

DOT (INTERNATIONAL AIR TRANSPORTATION ASSOCIATION)

PROPER SHIPPING NAME : Paint, flammable liquid
HAZARDS CLASS : 3
UN/NA NUMBER : UN1263
PACKING GROUP : PG II
EMERGENCY RESPONSE GUIDE (ERG) : 127

IMDG (OCEAN)
PROPER SHIPPING NAME : Paint, flammable liquid
HAZARDS CLASS : 3
UN/NA NUMBER : UN1263
PACKING GROUP : PG II
EMERGENCY RESPONSE GUIDE (ERG) : 127

MARINE POLLUTANT : No
SPECIAL PRECAUTIONS : P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P235 Keep cool.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

All ingredients in Section #3 are TSCA (Toxic Substance Control Act) listed.

OSHA HAZARDS : Flammable liquid, Moderate skin irritant, Moderate eye irritant, Carcinogen.
EPCRA - Emergency
CERCLA REPORTABLE QUANTITY

SARA 304 Extremely Hazardous Substances Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)
SARA 311/312 Hazards : Fire Hazard, Acute Health Hazard, Chronic Health Hazard
SARA 313 :

CLEAN AIR ACT :

INTERNATIONAL REGULATIONS

CLASSIFICATION ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP) :

Flam. Liq. Cat3; H226
Acute Tox. inhalation, Cat. 3; H331
Acute Tox. oral, Cat. 4; H302
Acute Tox. dermal, Cat. 3; H311
STOT SE, inhalation, Cat. 1; H372
STOT RE, inhalation, Cat. 1; H372
Skin Sens. Cat 1; H317
Skin Corrosion, Cat 1C; H314
Serious Eye Damage, Cat 1; H318
Germ Cell Mutagenicity, Cat 2; H341
Reproductive Toxicity, Cat 1B, H360
Acute Aquatic Toxicity, Cat 1; H400
Chronic Aquatic Toxicity, Cat1; H410

NATIONAL REGULATIONS

Indicates a chemical listed by IARC as a possible carcinogen.

STATE REGULATIONS

CALIFORNIA PROPOSITION 65

*This product contains (a) chemical (s) known to the State of California to cause cancer.

#This product contains (a) chemical (s) known to the State of California to be carcinogenic.

+This product contains (a) chemical (s) known to the State of California to cause birth defects or other reproductive harm.

Massachusetts Right to Know

This product contains	Chemical CAS#
Acetylacetone	123-54-6

Pennsylvania Right to Know


This product contains	Chemical CAS#
Dibutyltin Dilaurate	77-58-7
Acetylacetone	123-54-6

New Jersey Right to Know

This product contains	Chemical CAS#
Dibutyltin Dilaurate	77-58-7
Acetylacetone	123-54-6

16. OTHER INFORMATION**HMIS RATING**

Health :	2*
Flammability :	3
Reactivity :	0
Personal Protection :	J

NFPA CODES

MANUFACTURER DISCLAIMER : The information contained in this Safety Data Sheet is considered to be true and accurate. Cardinal Industrial Finishes makes no warranties, expressed or implied, as to the accuracy and adequacy of this information. This data is offered solely for the user's consideration, investigation and verification.